



FOLIANTEU, s.r.o.  
Stefanikova 1347/III  
293 01 Mlada Boleslav  
Czech Republic  
tel +420 326 370 711  
[foliant@foliant.eu](mailto:foliant@foliant.eu) | [www.foliant.eu](http://www.foliant.eu)

# FOLIANT POLLUX 760 SF

The FOLIANT Pollux 760 SF is a high speed compact industrial laminating machine, a heavy duty construction machine with a suction feeder and a high speed bump separator, with a walk-in service section and with an optional pallet feeder, a pallet stacker and an electric film loader/manipulator. **The machines maximum speed is up to 50 m/min.**, while the maximum performance is 3000 sheets per hour of a B1 portrait or 6000 sheets per hour of B2 landscape (white paper 200 gsm).



## FEEDER

The FOLIANT Pollux 760 SF is equipped with a rising pile back separation stream feeder, with a suction feed head. It is driven by an Omron servo motor and controlled by a machine central PLC. The Becker vacuum pump is used for sheets back and sides airing. The overlaps are electronically controlled, in an „in-run“ automatic mode, from the touch screen. The accuracy is +/- 2 mm under-lap (in a constant speed). The standard feeder is fitted with a lifting plate and its capacity is a 55 cm pile of paper.

## LAMINATOR

The FOLIANT Pollux 760 SF laminator maximum sheet size is 76 x 110 cm. The minimum sheet size is 30 x 25 cm (A4). FOLIANT Pollux 760 SF machine is a single sided thermal industrial laminator, laminating the paper 115 – 600 gsm, with an unique „U“ cross bar for the thin sheets flat and safety high pressure lamination, mounted in the front of the main laminating rollers, with an „In run“ adjustable de-curl bar.

The roll of a film is mounted on an air shaft that allows very convenient, easy and precise film positioning. The shaft capacity is up to 3000 m of the 24 - 31 microns film. The film holder unit is equipped with a trim slit and a perforating wheel.

The laminating process is done between two laminating rollers - a highly polished chrome roller, and a lower hard rubber pressure roller. The laminating roller is heated with 6 contact electric heaters inside the roller, with a sensitive in-roll temperature sensor. The pressure is pneumatically adjustable, with an extra independent control knob for each roller edge. The pressure of pulling rollers is controlled with a pneumatic control knob. There is a service „walk-in“ section between the machine laminating rollers and pulling rollers for an easy machine maintenance and rollers cleaning. The machine requires an external source of pressured air 200 l / min, 6 – 8 bars.

The machine is fitted with OMRON Programmable Logic Controllers, which controls all machines' functions. Used PLC system includes many automatic items for an easy machine control and a reliable lamination. The whole machine is controlled by an interactive easy understandable icon touch screen panel – no language version is needed.

## SEPARATOR

The integrated bump separator (sheeter) is equipped with a pair of fast cycling rollers. The process is controlled from the machine PLC unit. The separated sheets are delivered through a high speed belt conveyor (for safety loading to the reception unit) into a vibrating jogger (optional) or a pallet stacker (optional).

## LAMINATING FILMS

The machine laminates the BOPP films (23 – 42 microns), Nylon films (max 35 microns) and PET films (max. 35 microns).

## OPTIONS

### JOGGER 760 (OPTIONAL)\*

It is an adjustable vibrating reception unit for the laminated sheets stocking. Its capacity is limited up to a 10 cm pile of sheets.

### PALLET STACKER (OPTIONAL)\*

It is a device equipped with a pallet trolley, pneumatically controlled from the machine PLC, which loads the laminated sheets into a high pile. Its capacity is 65 cm pile of sheets. It is based on a manual scissors lift table (hydraulic) and sensors for its pneumatic control. The pallet can be manipulated either from the operator's side (it saves the manipulation space) or from behind.

### PALLET FEEDER (OPTIONAL)

It is fitted with a pallet holder and an adaptor for a full pallet of paper. Its capacity is a 65 cm paper pile. The pallet can be manipulated from the front and it requires another space for the manipulation.

### FILM LOADER/MANIPULATOR (OPTIONAL)

It is an electric lift with a film core adaptor for loading heavy rolls of film (max. capacity 125 kg). The device is not integrated with the machine. It is only connected with the machine's electric circuits.

\*Important – the machine must be operated either with a Pallet Stacker or with a Jogger.



Optional Pallet Feeder



Optional Pallet Stacker



Optional Jogger

#### Foliant Pollux 760 SF

<b>Max Speed</b>	50 m / min	<b>Film Micro Adjustment Air Shaft</b>	Standard
<b>Max Performance</b>	3000 B1 / hour	<b>Warming up Time</b>	8 min
<b>Feeding</b>	Automatic	<b>Temperature Control</b>	80 - 140°C
<b>Feeding System</b>	Suction Feeder	<b>Power Supply</b>	3 ph., 400 V AC, 50-60 Hz
<b>Feeder's Load Capacity</b>	55 cm	<b>Power</b>	12000 W
<b>Overlaps</b>	Automatic, PLC Control	<b>Floor space (w x l)</b>	165 x 395 cm
<b>Overlaps Accuracy</b>	+ / - 2 mm	<b>Weight</b>	990 kg
<b>Separation</b>	Automatic, Bump Rollers	<b>Pallet Feeder</b>	Optional
<b>Paper Weight</b>	115 - 600 gsm	<b>Pallet Feeder's Capacity</b>	65 cm
<b>Main Rollers Pressure</b>	Pneumatic	<b>Jogger 760</b>	Optional
<b>External Compressor</b>	200 l/ min, 6 - 8 bar	<b>Pallet Stacker</b>	Optional
<b>Min Sheets Size (w x l)</b>	30 x 25 cm	<b>Pallet Stacker Capacity</b>	65 cm
<b>Max Sheets (w x l)</b>	76 x 110 cm	<b>Film Loader (Electric)</b>	Optional