



# rotec<sup>®</sup> Premium Sleeve

High-quality sleeve with superior dimensional stability, especially developed for low tolerance applications and special quality requirements

Available wall thicknesses from 10 mm to 100 mm  
Special sizes available on request

## Product advantages


- **Highest dimensional stability for excellent results**
  - long-lasting and consistent register accuracy
  - permanently identical printing properties
  - constant parallelism of the sleeve
- **Proven to provide lowest tolerances**
  - constant outer diameter at fluctuating temperatures or high air humidity
  - high precision grinding for tight runout tolerance (TIR ≤ 0.02 mm, measured on carrier cylinder at TIR ≤ 0.005 mm)
  - face length according to DIN ISO 2768 T1 c
- **Meets all requirements of high quality printing**
  - perfect for high printing speeds
  - suitable for repeat length increases up to 600 mm
  - high wall thicknesses and sleeve lengths available
- **Easy and reliable handling**
  - long-lasting continuous mounting characteristics
  - easy adhesive tape dismounting
  - generally scratch and solvent resistant, if handled correctly (see rotec<sup>®</sup> User's Advice)

## Premium upgrades

- **rotec<sup>®</sup> Ω-surface technology\***  
provides full surface conductivity, guaranteed for 10 years
- **rotec<sup>®</sup> Register Ring**  
stainless steel register ring for lasting protection of sleeve base and register notch
- **rotec<sup>®</sup> End Seal**  
protects both sleeve ends with premium PU layer from damage, solvent, moisture etc.

# rotec® Premium Sleeve

## Available premium upgrades



rotec®  $\Omega$ -surface technology

rotec® Register Ring

rotec® End Seal

## Product specifications

Runout tolerance	TIR $\leq$ 0.02 mm (measured on carrier cylinder at TIR $\leq$ 0.005 mm)
Diameter tolerance	$\pm$ 0.02 mm
Face-length tolerance	according to DIN ISO 2768 T1 c
Wall thicknesses	from 10 mm to 100 mm special sizes available on request
Repeat length increases	up to 600 mm
Lengths	standard: up to 2400 mm special sizes: up to 3700 mm
Diameters	nearly all diameters
Material	extremely durable polyurethane surface (75 Shore D) proven rotec® interior design of synthetic resin and fibre compound
Adapters	can be combined with various types of adapters
Notch	available with metal-reinforced notch
Printing plates	suitable for all plate thicknesses
Adhesive tapes	suitable for all compressible tape types and thicknesses
Handling	generally scratch and solvent resistant (if handled correctly – see rotec® User's Advice)

\* The regulations of ATEX 95 concerning electrostatic derivation ability are fulfilled.

**You are welcome to contact us for further information.**

**Flint Group Flexographic Products**  
Solmsstraße 83  
48683 Ahaus  
Germany

T +49 711 9816-301  
F +49 711 9816-801  
info.flexo@flintgrp.com  
www.flintgrp.com

All information in this document is based on our present knowledge and experience at the time of printing. Due to the multitude of factors influencing the processing and application of our products, it does not exempt the user from testing and calibrating. Nor does it imply any legally binding assurance concerning specific properties of the products or the suitability for a particular application. The responsibility of observing any possible industrial property rights, laws and regulations is the obligation of the user. Subject to technical changes without prior notice. Product names marked ® are registered trademarks of Flint Group.